



# Antifreeze Universal BS ready for use -38°C

Ready-for-use Permanent Coolant (Colour: blue)

## Description:

**Antifreeze Universal BS ready for use -38°C** based on monoethylene glycol, it is a ready-made permanent coolant for operating in summer and in winter, with antifreeze and rust protection (all-year operation).

**Antifreeze Universal BS ready for use -38°C** is free of nitrites, amines and phosphates.

## Characteristics:

- Protection against corrosion for all parts of the cooling system made of the materials steel, gray iron, aluminium, copper, brass, soft solder.
- Avoidance of cavitation damages, such as on the coolant pump
- Compatibility with varnishes
- Compatibility with hose and sealing materials
- Avoidance of sediments, which can cause radiator plugging
- Avoidance of foaming

## Usage:

**Antifreeze Universal BS ready for use -38°C** is because of its specially used additives excellently suitable for aluminium, light alloy and gray iron motors (please observe manufacturer's instructions).

Depending on the type and the manufacturer's instructions the contents of the cooling system shall be replaced every 2 to 3 years

## Usable for:

We recommend this product for:	
AFNOR	NF-R 15-601 Type 1
AS	2108
ASTM	D 3306
ASTM	D 4985
BS	6580
CUNA	NC 956-16
JIS	K 2234
ÖNORM	V 5123
SAE	J 1034
UNE	26361

## Miscibility:

- **Antifreeze Universal BS ready for use -38°C** is miscible with most coolants on the basis of ethylene glycol. To avoid the formation of sludge it is recommended to use pure **Antifreeze Universal BS ready for use -38°C**.

Antifreeze Universal BS ready for use -38°C		
Article No.	Packaging unit	
STL 3100 002	Can	1 L
STL 3100 003	Can	1500 ml
STL 3100 004	Can	5 L
STL 3100 005	Can	20 L
STL 3100 006	Drum	60 L
STL 3100 008	Drum	200 L
STL 3100 009	PE-Container	1000 L

Data are subject to change.

Attention: Service instructions should be observed!

STL/WINTER/-  
09/2016