



JAGO MAR 2T

Motor Oil for all 2-Stroke Outboard-Motors

Description:

JAGO MAR 2T is specially designed for all 2-stroke outboard engines developed ashless two-stroke oil that meets NMMA TC-W3.

Characteristics

- Excellent protection against rust and corrosion
- Can easily be mixed with gasoline
- High wear protection
- Extraordinary lubrication
- High oxidation stability
- Ash-free formula

Usable for

NMMA (BIA)	TC-W3
------------	-------

Effects

- Optimal operating reliability
- Prevents against deposits - spark-plug bridge formation
- Environment-friendly - low smoke formation
- Selfmixing in tank
- Selfmixing and for separate lubrication

Utilization

- All 2-stroke petrol outboard engines, jet skis, Personal Watercraft
- Typical mixture ratio of 1:50 - 2% (ideally lead-free) (Follow manufacturer's recommendation)

Disposal:

- JAGO MAR 2T is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- JAGO MAR 2T is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill JAGO MAR 2T only.

JAGO MAR 2T

Article No.	Packaging unit	
STL 1050 122	Can	1 L
STL 1050 124	Can	5 L
STL 1050 125	Can	20 L
STL 1050 126	Drum	60 L
STL 1050 128	Drum	200 L
STL 1450 129	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	876
Viscosity at 40°C	mm ² /s	35,6
Viscosity at 100°C	mm ² /s	6,29
Viscosity index		126
Flash point PM	°C	107
Pourpoint	°C	-30
TBN	mgKOH/g	8,7
Colour		Brown

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/2T/-
07/2021