



JAGO XM 4T

High-Performance-Motorcycles-Motor Oil 20W50

Description:

JAGO XM 4T is a high performance special engine oil for motorcycles with air- or water-cooled 4-stroke engines. The high additive content guarantees optimum lubrication under extreme operating conditions. The ideal partner for sporty high- tech motorcycles in touring operations on all roads as well as off road.

Characteristics

- High oxidation stability
- Excellent high temperature characteristics
- High safety potential, also at boundary lubrication conditions
- Maximum shear stability

Usable for

SAE	20W-50
API	SN Plus
ACEA	A3
We recommend this product for:	
JASO	MA2

Disposal:

- **JAGO XM 4T** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **JAGO XM 4T** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **JAGO XM 4T** only.

Effects

- High operating reliability
- Prevents black sludge formation
- Low oil consumption
- High wear stability
- No clutch picking, secure function of wet clutches.

Utilization

- Large volume 4-stroke motorbike engines

JAGO XM 4T

Article No.	Packaging unit	
STL 1050 502	Can	1 L
STL 1050 504	Can	5 L
STL 1050 505	Can	20 L
STL 1050 506	Drum	60 L
STL 1050 508	Drum	200 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	879
Dynamic viscosity at -15°C	mPa.s	6980
Viscosity at 40°C	mm ² /s	148
Viscosity at 100°C	mm ² /s	18,8
Viscosity index		144
Flash point COC	°C	228
Pourpoint	°C	-27
Sulphate ashes	%	-
TBN	mgKOH/g	10,5

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/4T/-
07/2021