

# CALANA SFL00

## Half-Flowing Lubrication Grease

### Description:

**CALANA SFL00** is a natural coloured, lithium saponified lubrication grease (fluid grease) of NLGI category 00/000. It contains additives to improve rust and oxidation protection and the adhesion and pressure susceptibility of the lubrication film. Because of its soft consistency it is suitable especially for supply of central lubrication with narrow cross-sectional production. As of its good water resistance and the good adhesion the **CALANA SFL00** will not be washed away from the lubrication points by spray water.

### Characteristics

- Good adhesion ability
- Improved oxidation protection
- Excellent rust protection
- Excellent pressure susceptibility
- Water resistant

### Effects

- Excellent lubrication properties
- High wear protection
- Safe operation of vehicles and machinery at all operating conditions
- All-year operation

### Technical data

Typical characteristics:

Temperature application range	-50°C up to +100°C
Short-termed	up to +110°C
NLGI-category	00/000
Term (DIN 51825):	KP00G-50
ISO 6743-9	L-XEBBB00

### Examples of use:

All trucks, coaches, construction machinery- agricultural and forestry machines etc. supplied with central lubrication equipment (Vogel, Tecalemit, etc.).

### CALANA SFL00

Article No.	Packaging unit	
STL 1100 303	Bucket	5 kg
STL 1100 307	Jokey	18 kg
STL 1100 305	Large tin can	25 kg
STL 1100 306	Drum	50 kg