

DOLGAN DOT 5.1

Synthetic High-performance Brake Fluid

Description:

DOLGAN DOT 5.1 is a high performance brake fluid especially developed for the requirements of modern passenger car brake-systems with disc or drum brakes.

Characteristics

- Boiling point > 270°C
- Clearly wet boiling point > 185 °C
- Viscosity index at -40°C max. 900 cSt
- Raised corrosion protection at high temperatures

Usable for

Brake Fluid	DOT 5.1
Exceeds	DOT 3, DOT 4
SAE	J 1704
FMVSS	116
ISO	4925 Class 5-1

Effects

- Substantial higher operational safety even after long duration of operation
- No delay in moving the brake at temperatures up to -40°C
- Improved brake conveniences and increased safety level

Utilization

- car brake system according to DOT 4 / DOT 5
- Especially recommended for vehicles with ABS braking system

Special Notes:

- Please store brake fluid only closed originally. Close tank of brake fluid airtightly straight after usage.
- Please unconditionally observe manufacturers information when refilling brake fluid.
- When refilling the hydraulic brake system absolute cleanliness is necessary.
- This fluid can cause damages at the paintwork.

Disposal:

- Brake fluid must be gathered and disposed separately. It may not be mixed with used oil.

Miscibility:

- **DOLGAN DOT 5.1** is well-tolerated to comparable brake fluids. However, to guarantee complete efficiency it is recommended to use only **DOLGAN DOT 5.1** when refilling.

DOLGAN DOT 5.1

Article No.	Packaging unit	
STL 1210 100	Can	250 ml
STL 1210 101	Can	500 ml
STL 1210 102	Can	1 L
STL 1210 104	Can	5 L
STL 1210 107	Can (tin)	5 L
STL 1210 105	Can	20 L
STL 1210 106	Drum	60 L
STL 1210 108	Drum	200 L