

STRATIX S2

Hightec-Multigrade-Motor Oil 15W40

Description:

STRATIX S2 is a new, ultra-modern and multi-functional multigrade engine oil for petrol and diesel engines in passenger cars and vans with and without turbochargers - also recommended for harsh operating conditions.

STRATIX S2 ensures reduced fuel and oil consumption thanks to its optimized formulation. Suitable for use the whole year round thanks to its viscosity range. Adding a special booster enhances the quality level to API SN, achieving improvements in stability against oxidation, protection against deposition, wear protection characteristics and low temperature behaviour. This ensures a cleaner engine and ultimately to a longer service life for it.

Characteristics

- Multigrade character
- High engine cleanliness
- Universally applied for all gasoline and diesel engines
- Best wear protection
- Excellent viscosity-temperature behaviour
- High safety potential, also at boundary lubrication conditions
- Ageing and viscosity stability
- Excellent detergent- and dispersant characteristics
- Low volatilization tendency
- High, stable viscosity index
- Optimal protection against corrosion, oxidation, wear and foaming

Usable for

SAE	15W-40
API	SN/CF
ACEA	A3/B4
We recommend this product for:	
MB	229.1
VW	501.01, 505.00

Effects

- All-year operation
- High operating reliability
- Prevents black sludge formation
- Very good cold starting properties
- Suitable for extended oil change intervals

Utilization

- Four-stroke petrol engine
- with turbo charging
- with multivalve-technology
- with catalyst technology
- passenger car and transporter diesel engines
- Suction diesel
- Turbo diesel
- CDI- HDI- and TDI-motors
- Direct-injection
- with catalyst technology

Disposal:

- **STRATIX S2** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **STRATIX S2** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **STRATIX S2** when refilling.

STRATIX S2

Article No.	Packaging unit	
STL 1090 722	Can	1 L
STL 1090 723	Can	4 L
STL 1090 724	Can	5 L
STL 1090 725	Can	20 L
STL 1090 726	Drum	60 L
STL 1090 728	Drum	200 L
STL 1490 729	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	866
Dynamic viscosity at -25°C	mPa.s	-
Viscosity at 40°C	mm ² /s	94
Viscosity at 100°C	mm ² /s	14
Viscosity index		157
Flash point COC	°C	-
Pourpoint	°C	-30
TBN	mgKOH/g	10,3

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
07/2021