

ALPHEX HM (HLP 10)

HLP Hydraulic Oil according DIN 51524, Part 2

Description:

ALPHEX HM (HLP 10) is optimum alloyed and is having a high performance level as well as a broad field of application within the whole industry. It especially distinguishes with good viscosity-temperature behaviour, high ageing stability and reliable corrosion protection. Effective additives provide an excellent wear protection under extreme loads, too (FZG-Test A/8,3/90 12th damage loading step). The behaviour against sealing materials is neutral.

Characteristics

- High pressure susceptibility
- Excellent wear protection
- High air and water separating property
- Very good viscosity temperature behaviour
- High ageing stability
- Neutral towards sealing materials
- Reliable corrosion protection

Effects

- High operation safety of hydraulic equipment
- Favourable operating properties
- High performance level

Usable for

DIN 51524/2	ISO VG 10 / HLP 10
ISO 11128	HM
MIL	H 24 459
AFNOR	NF E 48-603 (HM)
FZG-Test	A8,3/90 12th damage loading step

Utilization

- Hydraulic equipment according DIN 51524
- for example: mobile hydraulics, pressing and forging plants, splash-pour-machines, a.o.

Disposal:

- ALPHEX HM (HLP 10) is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- ALPHEX HM (HLP 10) of HLP range is well-tolerated with comparable lubrications and can be mixed. However, it is recommended to take only ALPHEX HM (HLP 10) of HLP range when refilling.

ALPHEX HM (HLP 10)

Article No.	Packaging unit	
STL 1030 025	Can	20 L
STL 1030 026	Drum	60 L
STL 1030 028	Drum	200 L
STL 1430 029	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	855
Viscosity at 40°C	mm ² /s	9,6
Viscosity at 100°C	mm ² /s	2,6
Viscosity index		>95
Flash point COC	°C	>175
Pourpoint	°C	-26
TAN	mgKOH/g	0,2