



# XANA 8STEP ATF

**Special-High-Performance-HC-Synthetic-Automatic-Transmission-Fluid**

## Description:

XANA 8STEP ATF is a modern high- performance ATF- automatic transmission fluid with a lowered viscosity based on the latest additive technology.

Due to the special composition with selected HC- synthetic oils and synthetic base oils (PAO), the special requirements of modern 6-, 8 and 9-step automatic transmissions are fulfilled in powerful sport utility vehicles (SUV) and vehicles of the upper middle sized class and the luxury class.

The high friction coefficient ensures a slip- free transmission of high torques.

## Characteristics

- Adapted friction coefficient for sporty gear changes
- Prevents annoying friction vibrations
- Outstanding friction characteristics
- Excellent low temperature switching behavior
- Extrem wear protection
- Highest oxidation and aging stability
- Minimal foaming
- Neutral towards sealing materials

## Usable for

We recommend this product for:	
BENTLEY	PY 112995PA
BMW	83 22 0 142 516
BMW	83 22 2 152 426
BMW	83 22 2 305 397
BMW	83 22 2 289 720
BMW	ATF 3+
CHRYSLER	68157995 AA
FIAT	9.55550-AV5
HYUNDAI/KIA	040000C90SG
JAGUAR	02JDE 26444
JAGUAR/LAND ROVER	Fluid 8432
LAND ROVER	LR023288 / 232289
LAND ROVER	TYK 500050
MASERATI	231603
MOPAR	68157995AA
VW/AUDI/VAG	G 055 005 A1/A2/A6, G 055 162 A2/A6, G 055 540 A2, G 060 162 A1/A2/A6)
ZF	Lifeguardfluid 8 (S671 090 312)
ZF	Lifeguardfluid 6 (S671 090 255)
ZF	TE-ML 11 (6 HP + 8 HP)

## Disposal:

- XANA 8STEP ATF is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- XANA 8STEP ATF is only miscible with comparable lubrications and well tolerated. However, to get full advantage of XANA 8STEP ATF it is recommendable to use XANA 8STEP ATF when refilling.

## Effects

- Lowered viscosity for improved fuel efficiency
- Optimal operating reliability at extreme conditions
- Best lubrication
- Protection against adhesions
- Keeps the gearbox clean
- Prolongs the life and performance of the gearbox
- Visco-stability under extreme conditions in the high temperature area

## Utilization

- Motor vehicle automatic transmission according service instructions
- Not suitable for use in DCT/DSG- or CVT-transmissions

Data are subject to change.

Attention: Service instructions should be observed!

STL/GE/AU/-  
08/2021

## XANA 8STEP ATF

Article No.	Packaging unit	
STL 1030 612	Can	1 L
STL 1030 615	Can	20 L
STL 1030 616	Drum	60 L
STL 1030 618	Drum	200 L
STL 1430 619	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	841
Viscosity at 40°C	mm <sup>2</sup> /s	29,3
Viscosity at 100°C	mm <sup>2</sup> /s	5,5
Viscosity index		162
Flash point COC	°C	-
Pourpoint	°C	-48
Colour		Green

