



JAGO SYN 4T

Premium-Fully Synthetic-Motorcycles-Motor Oil 5W40

Description:

JAGO SYN 4T is a high-performance premium full synthetic engine oil for 4-stroke motorbikes. For highest demands at racings and for every day. Absolute lubrication reliability even at extremst stress. Maximum of wear protection at extremely loaded lubrication film.

Also well suitable for oil bath clutches.

No slip, stick and / or rough shifting of clutch discs.

Characteristics

- High wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Prevents black sludge formation
- Low volatilization loss

Effects

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Optimal engine cleanliness
- Low oil consumption
- Suitable for use at racing, streets and grounds
- Also for wet clutches

Usable for

SAE	5W-40
API	SL
We recommend this product for:	
JASO	MA2, MA

Utilization

- High-performance and normal 4-stroke motorbikes

Disposal:

- **JAGO SYN 4T** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **JAGO SYN 4T** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **JAGO SYN 4T** it is recommendable to use only **JAGO SYN 4T** when refilling.

JAGO SYN 4T		
Article No.	Packaging unit	
STL 1050 822	Can	1 L
STL 1050 824	Can	5 L
STL 1050 825	Can	20 L
STL 1050 826	Drum	60 L
STL 1050 828	Drum	200 L

Typical characteristics:		
Specific weight at 15°C	kg/m ³	845
Dynamic viscosity at -30°C	mPa.s	4200
Viscosity at 40°C	mm ² /s	81,5
Viscosity at 100°C	mm ² /s	14,0
Viscosity index		167
Flash point COC	°C	220
Pourpoint	°C	-45
Sulphate ashes	%	0,94
TBN	mgKOH/g	7,7

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/4T/-
02/2018